

Uses

- For a high build re- and new lacquering, to seal a repair.
- To be used on wood, plastic and metal surfaces.
- The additive 'ProSilicone' ensures a flawless lacquer creation.
- Recommended for both interior and exterior use.

Characteristics

- Manufactured on acrylic base.
- A transparent lacquer.
- Free from silicone.
- Gloss levels: deep matt 3-4, matt 10-13, silk matt 19-21, silk gloss 35-40, gloss 55-65, high gloss >75.
- Lightfast and weather resistant.
- Limited PVC-resistance (door and window gaskets).
- Good resistance and adhesion properties.

Application

Shake can well before use and briefly spray valve free. Check compatibility and adhesion on an inconspicuous area first. Spray distance approx. 30 cm. Surface has to be clean and free from grease. If necessary, make a pre-treatment (sand lightly and remove sanding residues). Spray on a wet coat of lacquer.

When sealing a repair with touch-up colours these will turn 'brighter' for a short while – as soon as lacquer has dried the original colour shade will return.

In case of vertical surfaces several thin coats are best. Allow lacquer to dry for approx. 20 minutes before recoating.

Specifications**Drying periods (at 20°C RT)**

- Dust-dry:** after approx. 15-20 minutes.
Touch-dry: after approx. 30 minutes.
Lightfastness: good up to very good.
Weather resistance: good up to very good.
Coverage: approx. 2 m² per 400 ml (single application).
Shelf life: at least 2 years (stored upright at room temperature, in original unopened container)

Safety Precautions

- Irritant.
- Irritating to eyes, skin and respiratory system.
- Extremely flammable.
- Pressurized container.
- Protect from sunlight and do not expose to temperatures exceeding 50°C.
- Do not spray on a naked flame or any incandescent material.
- Keep away from sources of ignition. – No smoking.
- Do not spray into eyes.
- Keep out of reach of children.

Extract of wordings of the law. For further information please see label and Material Safety Data Sheet.

Disposal


- Dispose of König aerosol cans only when completely emptied according to the official rules. For information please ask your local waste industry office.
- Material leftovers to be disposed of according to the European Waste Code 160505 – *gases in pressure containers other than those mentioned in 160504.*
- Heinrich König & Co. KG take care of the disposal of König aerosol cans, provided they are returned 'carriage paid' to the address stated below.

Packaging

150 ml/400 ml aerosol can
6 gloss levels (deep matt up to high gloss)

*Further information and Material Safety Data Sheet on the internet at
www.heinrich-koenig.de*

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for his or her particular purpose(s).

**Heinrich König & Co. KG**

An der Rosenhelle 5 • D-61138 Niederdorfelden
Phone: 0 61 01 - 53 60 0 • Fax: 0 61 01 - 53 60 11
E-mail: info@heinrich-koenig.de

Issue 44/06