

König AQUA Wood Filler A15500

Uses

- To fill small cracks and open joints of 1-3 mm depth.
- To be used on untreated or primed veneer and solid woods, laminate, MDF and metal.
- Recommended for indoor use – if used outside it has to be lacquered over.

Characteristics

- Coloured 1-component filler paste.
- All colour shades can be mixed.
- Drying period: approx. 30-60 minutes.
- Heat-resistant up to 100°C.

Application

If the desired colour shade is not available among the 10 standards, apply several colours on the Mixing Palette 609 and mix the desired shade with the working spatula. Fill paste into damaged area (suitable for depths of 1-3 mm).

Important: Work in two steps.

1st step: Firmly press in filler paste.

2nd step: Slightly overfill damaged area.

After drying (drying time: approx. 30-60 minutes – with a hair drier approx. 5-10 minutes) remove projectings with the Metal Planer and sand with 180-240 grit Dry Sandpaper. When working on delicate surfaces (closed-porous) re-sand with 1,800-12,000 grit Micro Sanding Paper (very fine). Apply Special Repair Lacquer PLUS 336-340 to protect damaged area from dust and dirt (spray distance approx. 30-40 cm). The AQUA Wood Filler is overcoatable with all König lacquers.

Note: Even weather-resistant, provided Furniture Lacquer PLUS 342-347 has been applied generously (create coat thickness!).

Specifications

Heat resistance: up to 100°C.

Mechanical stability: good.

Curing time: 30-60 minutes for a 1-3 mm thick coat – with a hair drier approx. 5-10 minutes.

Substrate material: untreated/primed veneer and solid wood, laminate, MDF and metal.

Overcoat: with all König lacquers.

Adhesion: good up to very good on all substrates mentioned above.

Shelf life: 1 year minimum (stored at room temperature, in original unopened container).

Protect from frost!

Safety Precautions

- Keep out of reach of children.

Disposal


- Dispose of container with the household waste only when completely empty or dried out.
- Material leftovers to be disposed of according to the European Waste Code 080410 – *waste adhesives and sealants other than those mentioned in 080409.*

Packaging

- Single tube 150 g + accessories (10 different colour shades available)
- Assortment of 10 colour shades

Further information and Material Safety Data Sheet on the internet at
www.heinrich-koenig.de

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for his or her particular purpose(s).



Heinrich König & Co. KG

An der Rosenhelle 5 • D-61138 Niederdorfelden

Phone 0 61 01-53 60 0 • Fax 0 61 01-53 60 11

info@heinrich-koenig.de

Issue 13/09