

Uses

- For the repair of polishable natural stone (not sandstone or porous limestone) and diverse engineered stones.
- Build-up and finish system especially for horizontal surface damages.
- To be used solely or in combination with other filler materials from the RepairLux® range.
- Recommended for indoor and outdoor use.

Characteristics

- A light-hardening filler material (LED).
- Cures in coats up to 3 mm.
- Low viscous.
- Clear transparent.
- Planable, sandable and polishable.
- High stability and resistance.
- Lightfast.
- Weather resistant.

Application

Ensure processing temperature is above +8°C (filler and surface). Do not apply in direct sunlight. Clean damaged area from dirt and loose particles using auxiliaries from the system. Fill damage in stages of 3 mm maximum and cure each coat individually. To imitate a crystalline structure and shadings, the filler can be combined with relevant Granulates (fine and coarse art.no. 403 020-025) and Colours (art.no. 403 006-019). In case of damage to edges, pre-treat with RepairLux® Transparent Base (good stability thanks to its thixotropic properties). If necessary, create a kind of formwork with adhesive tape and cover the repair with RepairLux® Transparent Liquid. Strip off excess and level surface with the Planer. Finally, adjust the gloss level using Micro Sanding Paper and Polishing Paste.

For detailed description of the individual system components and their use, please refer to the instructions for use.

Specifications

- Hardening period:** 30 secs/cm².
Hardening coat: 3 mm maximum (construction).
Temperature resistance: for a short time up to 150°C.
Shelf life: at least 2 years
(stored in original unopened container and lightproof at 2-28°C)

Safety Precautions

- Irritant.
- Irritating to eyes, respiratory system and skin.
- Having come into contact with eyes rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of water and soap.
- For professional use only.

Extract of wordings of the law. For further information please see label and Material Safety Data Sheet.

Disposal

- Leftover materials and containers to be disposed of according to official regulations, when completely emptied. For detailed information please ask your local waste industry office.
- Cured product is an inert plastic material which can be disposed of according to the local official regulations.
- European Waste Code for uncured material: 080409.

Packaging

3ml syringe

*Further information and Material Safety Data Sheet on the internet at
www.repairlux.de | www.heinrich-koenig.de*

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for his or her particular purpose(s).



®
Seit 1892

Heinrich König & Co. KG

An der Rosenhelle 5 • D-61138 Niederdorfelden

Phone: 0 61 01-53 60 0 • Fax: 0 61 01-53 60 11

E-mail: info@heinrich-koenig.de

Issue 17/09