

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 641000
Print date: 05.08.2021
Version: 3.1

Special Polyester Lacquer
Revision date: 05.08.2021
Issue date: 05.08.2021

53361 GB
Page 1 / 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. product identifiers

Article No. (manufacturer/supplier) 641000
Trade name/designation Special Polyester Lacquer
UFI: EQ78-JU18-G10W-TFAF

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Polyester mastic

Uses advised against:

Do not use for products which come into contact with the food stuffs.

1.3. Details of the supplier of the safety data sheet

Manufacturer/supplier

Heinrich König GmbH & Co.KG
An der Rosenhelle 5
D-61138 Niederdorfelden

Telephone: +49 6101 5360 0
Telefax: +49 6101 5360 11
E-mail: Info@heinrich-koenig.de
Website: www.heinrich-koenig.de

Department responsible for information:

Laboratory

Only available during office hours:

Telephone: +49 6101 5360 71
Mon - Thurs 08:00 to 16:00
Friday 08:00 - 12:30

E-mail (competent person)

SDB@heinrich-koenig.de

1.4. Emergency telephone number

Emergency telephone number

Emergency CONTACT (24-Hour-Number): GBK
GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 3 / H226

Flammable liquids

Flammable liquid and vapour.

Skin Irrit. 2 / H315

Skin corrosion/irritation

Causes skin irritation.

Eye Irrit. 2 / H319

Serious eye damage/eye irritation

Causes serious eye irritation.

Skin Sens. 1 / H317

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Repr. 2 / H361d

Reproductive toxicity

Suspected of damaging the unborn child.

STOT SE 3 / H335

STOT-single exposure

May cause respiratory irritation.

STOT RE 1 / H372

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aquatic Chronic 3 / H412

Hazardous to the aquatic environment

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H226

Flammable liquid and vapour.

H315

Causes skin irritation.

H319

Causes serious eye irritation.

H317

May cause an allergic skin reaction.

H361d

Suspected of damaging the unborn child.

H335

May cause respiratory irritation.

H372

Causes damage to organs through prolonged or repeated exposure.

H412

Harmful to aquatic life with long lasting effects.

Precautionary statements

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 641000 Special Polyester Lacquer
Print date: 05.08.2021 Revision date: 05.08.2021 53361 GB
Version: 3.1 Issue date: 05.08.2021 Page 2 / 10

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe vapour.
P280 Wear protective gloves and eye/face protection.
P370 + P378 In case of fire: Use foam to extinguish.
P403 + P235 Store in a well-ventilated place. Keep cool.

Hazard components for labelling

maleic anhydride
Styrene

Supplemental hazard information

No further relevant information available.

2.3. Other hazards

No information available.

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Description 2-Component filler

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No.	REACH No.	
CAS No.	Designation	weight-%
Index No.	classification // Remark	
202-851-5	01-2119457861-32-xxxx	
100-42-5	Styrene	25 < 50
601-026-00-0	Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Repr. 2 H361d / STOT SE 3 H335 / STOT RE 1 H372 / Asp. Tox. 1 H304 / Aquatic Chronic 3 H412 / Flam. Liq. 3 H226	
203-571-6	01-2119472428-31-xxxx	
108-31-6	maleic anhydride	< 0,0015
607-096-00-9	Acute Tox. 4 H302 / STOT RE 1 H372 / Skin Corr. 1B H314 / Eye Dam. 1 H318 / Resp. Sens. 1 H334 / Skin Sens. 1A H317 Specific concentration limit (SCL): Skin Sens. 1A H317 >= 0,001	

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 641000
Print date: 05.08.2021
Version: 3.1

Special Polyester Lacquer
Revision date: 05.08.2021
Issue date: 05.08.2021

53361 GB
Page 3 / 10

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 641000
Print date: 05.08.2021
Version: 3.1

Special Polyester Lacquer
Revision date: 05.08.2021
Issue date: 05.08.2021

53361 GB
Page 4 / 10

Occupational exposure limit values:

Styrene

Index No. 601-026-00-0 / EC No. 202-851-5 / CAS No. 100-42-5

TWA: 430 mg/m³; 100 ppm

STEL: 1080 mg/m³; 250 ppm

Additional information

TWA : Long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

Styrene

Index No. 601-026-00-0 / EC No. 202-851-5 / CAS No. 100-42-5

DNEL short-term oral (acute), Workers: 306 mg/kg

DNEL long-term dermal (systemic), Workers: 406 mg/kg

DNEL acute inhalative (local), Workers: 289 mg/m³

DNEL acute inhalative (systemic), Workers: 289 mg/m³

DNEL long-term inhalative (systemic), Workers: 85 mg/m³

DNEL long-term oral (repeated), Consumer: 2,1 mg/kg

DNEL long-term dermal (systemic), Consumer: 343 mg/kg

DNEL acute inhalative (local), Consumer: 174,25 mg/m³

DNEL long-term inhalative (systemic), Consumer: 10,2 mg/m³

maleic anhydride

Index No. 607-096-00-9 / EC No. 203-571-6 / CAS No. 108-31-6

DNEL acute inhalative (local), Workers: 0,2 mg/m³

DNEL acute inhalative (systemic), Workers: 0,2 mg/m³

DNEL long-term inhalative (local), Workers: 0,081 mg/m³

DNEL long-term inhalative (systemic), Workers: 0,081 mg/m³

PNEC:

Styrene

Index No. 601-026-00-0 / EC No. 202-851-5 / CAS No. 100-42-5

PNEC aquatic, freshwater: 0,028 mg/L

PNEC aquatic, marine water: 0,014 mg/L

PNEC aquatic, intermittent release: 0,04 mg/L

PNEC sediment, freshwater: 0,614 mg/kg

PNEC sediment, marine water: 0,307 mg/kg

PNEC, soil: 0,2 mg/kg

PNEC sewage treatment plant (STP): 5 mg/L

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

Suitable respiratory protection apparatus: A

Hand protection

For prolonged or repeated handling the following glove material must be used: FKM (fluoro rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 641000
Print date: 05.08.2021
Version: 3.1

Special Polyester Lacquer
Revision date: 05.08.2021
Issue date: 05.08.2021

53361 GB
Page 5 / 10

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state: Liquid
Colour: colourless

Odour: characteristic

Odour threshold: not determined

pH at 20 °C: N.A.

Melting point/freezing point: n.a.

Initial boiling point and boiling range: 145 °C
Method: calculated.

Flash point: 32 °C
Method: calculated.

Evaporation rate: not determined

flammability

Burning time: not determined

Upper/lower flammability or explosive limits:

Lower explosion limit: 1,2 Vol-%
Method: calculated.

Upper explosion limit: 8,9 Vol-%
Method: calculated.

Vapour pressure at 20 °C: 6 mbar
Method: calculated.

Vapour density: not determined

Relative density:
Density at 20 °C: 1,11 g/cm³
Method: calculated.

Solubility(ies):

Water solubility at 20 °C: insoluble

Partition coefficient: n-octanol/water: see section 12

Auto-ignition temperature: 480 °C
Method: DIN 51794

Decomposition temperature: not determined

Viscosity at 20 °C: 85 s 4 mm
Method: DIN 53211

Explosive properties: not determined

Oxidising properties: not determined

9.2. Other information

Solid content: 100,00 weight-%

solvent content:

Organic solvents: 0 weight-%

Water: 0 weight-%

Solvent separation test: < 3 weight-% (ADR/RID)

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 641000
Print date: 05.08.2021
Version: 3.1

Special Polyester Lacquer
Revision date: 05.08.2021
Issue date: 05.08.2021

53361 GB
Page 6 / 10

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

11.1. Information on toxicological effects

Acute toxicity

Styrene

oral, LD50, Rat: 2650 mg/kg
inhalative (vapours), LC50, Rat: 12 mg/L (4 h)
Harmful if inhaled.

maleic anhydride

oral, LD50, Rat: 1090 mg/kg ; Evaluation Harmful if swallowed.
Method: OECD 401
dermal, LD50, Rabbit: 2620 mg/kg

Skin corrosion/irritation; Serious eye damage/eye irritation

Causes skin irritation.

Causes serious eye irritation.

Styrene

Skin (4 h)

Prolonged or repeated contact with the preparation can lead to irritations of mucous membranes and of skin such as redness, formation of blebs, dermatitis, etc..; Irritating to skin.

eyes

Irritation

maleic anhydride

Skin (4 h)

Method: OECD 404

Causes severe skin burns and eye damage.

eyes

Method: OECD 405

Causes serious eye damage.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

maleic anhydride

Skin: ; Evaluation May cause an allergic skin reaction.

Method: OECD 429

Respiratory system: ; Evaluation May cause allergy or asthma symptoms or breathing difficulties if inhaled.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Suspected of damaging the unborn child.

Styrene

Reproductive toxicity

Suspected of damaging the unborn child.

STOT-single exposure; STOT-repeated exposure

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 641000
Print date: 05.08.2021
Version: 3.1

Special Polyester Lacquer
Revision date: 05.08.2021
Issue date: 05.08.2021

53361 GB
Page 7 / 10

May cause respiratory irritation.

Causes damage to organs through prolonged or repeated exposure.

Styrene

Specific target organ toxicity (single exposure), Irritation

May cause respiratory irritation.

Specific target organ toxicity (repeated exposure)

Causes damage to organs through prolonged or repeated exposure.

maleic anhydride

Specific target organ toxicity (repeated exposure) Evaluation Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

Styrene

Aspiration hazard

May be fatal if swallowed and enters airways.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

12.1. Toxicity

Styrene

Fish toxicity, LC50, *Lepomis macrochirus* (Bluegill): 25 mg/L (96 h)

Daphnia toxicity, EC50, *Daphnia magna* (Big water flea): 4,7 mg/L (48 h)

Fish toxicity, LC50, *Pimephales promelas* (fathead minnow): 32 mg/L (96 h)

Algae toxicity, IC50, *Pseudokirchneriella subcapitata*: 0,72 mg/L (96 h)

Based on available data the classification criteria are not met.

Long-term Ecotoxicity

Harmful to aquatic life with long lasting effects.

Styrene

Fish toxicity, LC50 (96 h)

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

Styrene

Biodegradation, OECD 301D/ EEC 92/69/V, C.4-E: 80 % (20 D)

Readily biodegradable (according to OECD criteria).

12.3. Bioaccumulative potential

Styrene

Partition coefficient: n-octanol/water: 2,95 - 3,16

Method: OECD 107

Based on the n-octanol/water partition coefficient accumulation in organisms is not expected.

12.4. Mobility in soil

Styrene

:

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 641000
Print date: 05.08.2021
Version: 3.1

Special Polyester Lacquer
Revision date: 05.08.2021
Issue date: 05.08.2021

53361 GB
Page 8 / 10

- 12.6. **Other adverse effects**
No information available.

SECTION 13: Disposal considerations

13.1. **Waste treatment methods**

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111* Waste paint and varnish containing organic solvents or other dangerous substances

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. **UN number**

UN 1866

14.2. **UN proper shipping name**

Land transport (ADR/RID): Resin solution
Sea transport (IMDG): RESIN SOLUTION
Air transport (ICAO-TI / IATA-DGR): Resin solution

14.3. **Transport hazard class(es)**

Land transport (ADR/RID): NO GOODS OF CLASS 3
FOR CONTAINERS > 450 l Class 3
Sea transport (IMDG) 3
for packages < = 450 litres: Transport in accordance with the provisions of paragraph 2.3.2.5 of the IMDG Code.
Air transport (ICAO-TI / IATA-DGR) 3

14.4. **Packing group**

III

14.5. **Environmental hazards**

Land transport (ADR/RID) No further relevant information available.
Marine pollutant No further relevant information available.

14.6. **Special precautions for user**

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

tunnel restriction code D/E

Sea transport (IMDG)

EmS-No. F-E, S-E

Polyester resin multi-component systems

For polyester resin multi-component systems (base + hardener), UN number 3269 must be used in accordance with GGVS / ADR and IMDG code.

14.7. **Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

SECTION 15: Regulatory information

15.1. **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 641000
Print date: 05.08.2021
Version: 3.1

Special Polyester Lacquer
Revision date: 05.08.2021
Issue date: 05.08.2021

53361 GB
Page 9 / 10

EU legislation

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

Maximum VOC content (g/L) of the product in a ready to use condition: 0

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Substance/product listed in the following inventories:

DSL listed
TSCA listed

REACH candidate list of substances of very high concern (SVHC) for the approval process.

According to the available data and / or according to the information provided by the suppliers, the product does not contain any substance that is eligible for inclusion in Annex XIV (list of substances subject to authorization) in accordance with Article 57 in conjunction with Article 59 of REACH.

Regulation (EC) 1907/2006. material in question applies.Regulation (EC) 1907/2006 (REACH) Annex XIV (list of substances subject to authorization)

According to the available data and / or according to the information provided by the suppliers, the product does not contain any substance that is considered to be a substance that requires authorization according to REACH Regulation (EC) 1907/2006 Annex XIV.

15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
202-851-5 100-42-5	Styrene	01-2119457861-32-xxxx
203-571-6 108-31-6	maleic anhydride	01-2119472428-31-xxxx

SECTION 16: Other information

Full text of classification in section 3

Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Repr. 2 / H361d	Reproductive toxicity	Suspected of damaging the unborn child.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
STOT RE 1 / H372	STOT-repeated exposure	Causes damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.
Flam. Liq. 2 / H226	Flammable liquids	Flammable liquid and vapour.
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Skin Corr. 1B / H314	Skin corrosion/irritation	Causes severe skin burns and eye damage.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
Resp. Sens. 1 / H334	Respiratory or skin sensitisation	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens. 1A / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3	Flammable liquids	On basis of test data.
Skin Irrit. 2	Skin corrosion/irritation	Calculation method.
Eye Irrit. 2	Serious eye damage/eye irritation	Calculation method.
Skin Sens. 1	Respiratory or skin sensitisation	Calculation method.
Repr. 2	Reproductive toxicity	Calculation method.
STOT SE 3	STOT-single exposure	Calculation method.
STOT RE 1	STOT-repeated exposure	Calculation method.
Aquatic Chronic 3	Hazardous to the aquatic environment	Calculation method.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 641000
Print date: 05.08.2021
Version: 3.1

Special Polyester Lacquer
Revision date: 05.08.2021
Issue date: 05.08.2021

53361 GB
Page 10 / 10

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

You can also find current SDSs for our standard products online on our homepage under **Downloads** in the relevant product area.