## König Colour Touch-Up

### 240 000

#### Intended Use

- To be used on wood, plastic and laminate surfaces.
- For the opaque touch-up by brush.
- For re-dyeing and for achieving basic shades in the wood shade sector.
- To cover the substrate in case of veneer sandthroughs.
- To colour Rex-Lith Transparent, Wood and White.
- For indoor and outdoor use.

#### **Characteristics**

- Pigmented acrylic-based covering lacquer.
- Dries rapidly.
- High opacity.
- Overcoatable with all König touch-up and aerosol lacquers.
- Good adhesion to many lacquer, plastic and metal surfaces (not to Soft-PVC).
- Limited PVC-resistance (window/door gaskets).
- Good lightfastness and weather-resistance.
- Gloss level: silk matt.
- Colours can be intermixed.

#### **Application Notes**

Shake up bottom sediments well before use. Rattle of mixing balls must be heard. Processed best at room temperature.

Get your special colour by mixing different colour shades (mixing palette). More colour brilliance can be achieved by 'firing' either with König Touch-Up Dye or with König Colour Concentrate.

#### **Physical Properties and Shelf Life**

Processing recommended: at 18-25°C and 55-65% RH Dust-dry: after approx. 1-2 minutes Touch-proof: after approx. 2-5 minutes (dependent on room temperature and coat thickness)

Lightfastness: Weather resistance: Shelf life: (dependent on room temperature and coat thickness) good good minimum 2 years (stored at room temperature, in unopened original container)

#### **Safety Precautions**

Please refer to label and material safety data sheet.

#### Disposal

- Do not allow product to enter drains or watercourses.
- Non-contaminated packaging may be recycled.
- Leftover material to be disposed of according to the European Waste Code 080111 – waste paint and varnish containing organic solvents or other dangerous substances.
- For more detailed information, please refer to the Material Safety Data Sheet for this product or ask your local waste industry office.

#### Packaging

On request.

# Further information and Material Safety Data Sheet on the internet at www.heinrich-koenig.de

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for his or her particular purpose(s).



Heinrich König & Co. KG An der Rosenhelle 5 • D-61138 Niederdorfelden Phone: 0 61 01-53 60 0 • Fax: 0 61 01-53 60 11 E-mail: info@heinrich-koenig.de

Issue 29/16